

The Main Concepts of the European Ground Systems – Common Core (EGS-CC)

Mauro Pecchioli, ESA/ESOC Juan María Carranza, ESA/ESTEC Presentation to GSAW March 2013

© 2013 by <u>esa</u>. Published by The Aerospace Corporation with permission.







Background

- Within Europe, different monitoring and control systems are used by different organisations
 - Some of them common to Mission Operations and Spacecraft Assembly, Integration and Testing (AIT), some specific
 - Often multiple systems are used even within the same mission by different companies or at different levels (e.g. payload/system) or in different phases
 - Little synergy across missions and mission phases
 - Difficult to exchange data between various stakeholders
- Many of the existing systems have reached or are reaching their end of life
 - Become excessively complex with time
 - Use old software technologies and hardware platforms
 - Are difficult to maintain and modernise



Objectives

- The EGS-CC Initiative aims at developing a common European M&C infrastructure enabling:
 - Seamless transition from spacecraft Assembly, Integration and Testing to Mission Operations
 - Overall cost reductions by sharing development, sustaining and maintenance of a single infrastructure
 - A reduction in the cost and risk associated to the implementation of space projects
 - The modernization of legacy Electrical Ground Support Equipment (EGSE) and Mission Control Systems (MCS)
 - The exchange of ancillary implementations across organizations



Stakeholders

- EGS-CC is a collaboration of European large system integrators and space agencies to develop a common core
 - Astrium Satellites
 - Astrium Space Transportation
 - CNES
 - DLR
 - ESA ESOC
 - ESA ESTEC
 - OHB System
 - Thales Alenia France
 - Thales Alenia Italy
- Initiative considered strategic by all parties




Collaboration Agreements

- Memorandum of Understanding between the EGS-CC partners
- Collaboration Agreement (legally binding) being finalised and signed
- Development of the EGS-CC in open competition according to ESA contract conditions and processes
- Adoption of the EGS-CC for institutional missions and then for commercial missions after successful operational validation in institutional missions
- Active stakeholders involvement at two levels:
 - Steering Board, owning the responsibility of defining and managing the implementation of policy related aspects (e.g. funding, procurement, evolution, licensing)
 - System Engineering Team, acting as a technical coordination body managing the definition and all technical aspects of the system










Main System Features

- Scope of the EGS-CC system features is very ambitious
 - Support of all mission types and phases
 - Open, component based, service oriented architecture
 - Generic and extensible functionality
 - High performance and scalability
 - Layered implementation
 - Clear separation between generic M&C functions (kernel) and specific features of the controlled system (adaptation layer)
 - Binary compatibility
 - Standardised interfaces (as far as possible...)
 - Technology isolation (as far as possible...)
 - Long term maintainability




Top Level Decomposition







Architectural Layers








Architectural Layers


ASTRIUM OHB

ThalesAlenia

SYSTEM



Architectural Layers





Kernel Functional Scope

- Application support layer
 - Run-time (component) framework
 - System management and administration
 - Access control (security)
 - Time synchronisation
 - Data archiving
- Monitoring and Control components
 - Monitoring and Control Model
 - Control activities validation, scheduling, execution and verification
 - Commanding (control of the controlled system)
 - Procedures execution
 - Reporting data (parameters) processing
 - Event processing
 - Support of live, playback, retrieval and replay processing modes



Reference Implementations Functional Scope

Adaptation layer

- TM/TC Data I/F handlers (based on CCSDS SLE)
- Monitoring and control adapters (e.g. TM/TC receiver/releaser, SCOE I/F Protocols)
- Modelling of M&C services of the controlled system (based on ECSS PUS)
- Space/Ground time correlation

User applications

- User desktop
- User defined displays (plots, synoptic, alphanumeric)
- M&C applications (control stacks, history logs, alarm summary display)
- System (administration and monitoring) displays
- M&C Model browser (navigation tree)

Off-line tools

- Preparation tools
- Basic post-processing and reporting
- External interfaces
 - Tailoring/configuration/archive data import/export
 - M&C services (based on CCSDS MO)
 - Many others (a long list...)








The Monitoring and Control Model

- Functional core of the system
- Provides capability to model the complete space system from a monitoring and control standpoint, based on the Space System Model concept of ECSS E-70-31
- Acts as an abstraction layer for monitoring and control operations (through a hierarchy of System Elements)
- Encapsulates the main monitoring and control functions (e.g. parameter processor, activities handler, events processor)
- Provides access to all data of M&C relevance (static definitions and dynamic state)
- Interacts with the engineering data archive to store all generated data of operational relevance for later retrieval/replay
- Supports the provision of M&C services to external components




Hierarchical M&C Model





MCM Data Access Layer




Data Processing Concept

ThalesAlenia

SYSTEM

Space




Data Processing Concept - LIVE


ThalesAlenia

SYSTEM


Space



Data Processing Concept - REPLAY




Data Processing Concept - RETRIEVAL






System Integration Concept

Legenda





Component Run-Time Platform






















System Integration Concept






System Integration Concept



System of Systems Approaches

- Independent EGS-CC System Instances
- Master / Child setup



Merged EGS-CC
System Instances



Technology Selection Process

- Significant use of 3rd party technologies/products but trying to avoid invasive dependencies
- Precise/severe technology selection criteria/constraints have been identified
- Areas where re-use of 3rd party technologies is expected identified (technology domains)
- Potential candidates for each domain identified
- Linux (+ Windows for the user front-end) and Java selected as basic technologies
- Final selection of the other technologies/products is taking place as part of the Technology Assessment activity taking place in Phase B
- Aim is to define the best fit of technologies meeting the EGS-CC needs (and not necessarily the best selection for each individual domain)



(Run-time) Technology Domains

- Component Framework
- Service Integration Platform
- Communication and Data Distribution
- System Run-Time Management
- Logging
- Security
- File Management
- Data Persistence
- Data Archiving
- Data Modeling and Tooling

- User Interface
- User Defined Displays
- Post Processing & Reporting
- Scripting
- Procedures Language
- Expression Language



Status and Plans

- Phase A has been recently completed outputs include
 - Domain analysis, Use cases, User (functional and nonfunctional) requirements, glossary, system concepts, conceptual architecture, external interfaces identification, preliminary technology assessment
- Phase B just started, including industrial support for:
 - Software Requirements Engineering and Architectural Design
 - Technological Proof of Concept
- Phase C/D expected to start in 2014
 - based on an incremental/iterative approach
 - continuous integration and validation of main deliverables in the target environments (Large System Integrators and Agencies)
- Operational validation through pilot projects for EGSE and MCS applications





- The EGS-CC initiative is in its early phases
- Strong stakeholders commitment
- Objectives are very ambitious but feasible
- The expected benefits justify the commitment and associated investments
- A phased approach to design and development has been adopted
- System definition (Phase A) completed
- System design (Phase B) just started
- First pilot projects expected to materialise in the 2015-2016 time horizon.





Thank you for your attention





Bonus Slides






Use/adoption of product standards

- TM/TC protocols (ECSS-E-ST-50-03 and 04) for packet based missions
- PUS (ECSS-E-ST-70-41) for missions implementing those services
- On-board control procedures (ECSS-E-ST-70-01)
- M&C data definitions (ECSS-E-ST-70-31)
- Procedures languages requirements (ECSS-E-ST-70-32)
- Standards for exchange of information like TM/TC Data definitions (e.g. XTCE)
- Standards related to services to be used or offered: MAL (CCSDS 521.0-B) and SLE (CCSDS 91x)
- Other standards relevant to the different types of subsystems with which EGS-CC will interface (e.g. MIL bus standards)
- Technology standards (methods and tools associated to the chosen technologies) for areas like:
 - Communications frameworks
 - Components/service frameworks
 - Data models






MCM Definition and Storage






Monitoring Overview






Control Operations Overview

SYSTEM



M&C Components Conceptual Architecture



Conceptual Data Model

EGS-CC Data Model

Product Structure	Monitoring & Control Model	Monitoring & Control Data
Func. Electr. Architecture	Procedure Data	Monitoring & Ctrl Validation
Display Data	Operational Modes	Archive
Engineering Category Definition		

Engineering Property Definition



EGS-CC System Deployment

